

1855ENH - 75 Ohm SDI Coax, Mini RG-59, 22 AWG, Solid BC, Foil + 90% TC Braid, LSZH Jkt

Item: 20119425 + 20119426



Product Overview

Suitable Applications

Digital Video, 6 Gb/s UHDTV, HD-SDI 1080p; Cable is UV-resistant and suitable for indoor and outdoor use

Construction Details

RG Type

Mini 59

CONDUCTOR

No. of Elements	Size	Stranding	Nom. Diameter	Material
1	22 AWG	Solid	0.65 mm	BC - Bare Copper

INSULATION

Element	Material	Nom. Insulation Diameter
Insulated Conductor	PE - Polyethylene (Foam)	2.9 mm (0.11 in)

OUTER SHIELD

Layer	Outer Shield Type	Material	Coverage
1	Tape	Tri-Laminate (Alum+Poly+Alum)	100%
2	Braid	Tinned Copper (TC)	90%

OUTER JACKET

Material	Nom. Diameter
LSZH - Low Smoke Zero Halogen (Flame Retardant)	4.45 mm

Table Notes

According to EN 50290-2-20

Electrical Characteristics

ATTENUATION

Frequency	Nom. Attenuation
1 MHz	1.7 dB/100m
3.6 MHz	2.5 dB/100m
5 MHz	2.8 dB/100m
6 MHz	3 dB/100m
7 MHz	3.2 dB/100m
10 MHz	3.7 dB/100m
12 MHz	4 dB/100m
25 MHz	5.4 dB/100m
67.5 MHz	8.3 dB/100m
71.5 MHz	8.6 dB/100m
88.5 MHz	9.5 dB/100m
100 MHz	10 dB/100m
135 MHz	11.5 dB/100m
143 MHz	11.9 dB/100m
180 MHz	13.2 dB/100m
270 MHz	16.1 dB/100m
360 MHz	18.6 dB/100m
540 MHz	22.8 dB/100m
720 MHz	26.4 dB/100m
750 MHz	26.9 dB/100m
1000 MHz	31.3 dB/100
1500 MHz	38.7 dB/100m
2000 MHz	45 dB/100m
2250 MHz	48 dB/100m
2500 MHz	50.8 dB/100m
3000 MHz	56.1 dB/100m
4000 MHz	65.7 dB/100m
4500 MHz	70.2 dB/100m

ELECTRICALS

Max. Conductor DCR	Nom. Capacitance Cond-to-Shield	Nom. Characteristic Impedance	Nom. Velocity of Prop.
55 Ohm/km (17 Ohm/1000ft)	53 pF/m (16 pF/ft)	75 Ohm	84%

TRANSFER IMPEDANCE

Frequency	Max. Transfer Impedance
5-30 MHz	Max. 15 mOhm/m

SCREENING

Frequency	Min. Screening Attenuation
30 - 1000 MHz	85 dB
1000 - 2000 MHz	
2000 - 3000 MHz	
3000 - 4500 MHz	
Screening Class	B

VOLTAGE

Voltage Rating
75 V DC

Mechanical Characteristics

TEMPERATURE

Operating	Installation	Storage
-30°C To +70°C	-5°C To +50°C	-30°C To +70°C

BEND RADIUS

Stationary Min.	
45 mm (1.8 in)	
Max. Pull Tension	160 N (36 lbf)

Standards and Compliance

Environmental Suitability	Indoor/Outdoor - Euroclass Dca
Flammability / Reaction to Fire	IEC 60332-1-2, CEI 20-35/1
CPR Compliance	CPR Euroclass: Dca-s1,d1,a1; CPR UKCA Class: Dca-s1,d1,a1
ISO/IEC Compliance	IEC 61034-2 - Smoke Density Min Transmittance = 60%
CENELEC Compliance	EN 50117-1EN 50290-2-20
European Halogen Free Standards	IEC 62821-1 Halogen Free Compliance = Yes, IEC 60754-1 - Halogen Amount = Zero, IEC 60754-2 - Halogen Acid Gas Amount - Max. Conductivity = 2.5 µS/mm, IEC 60754-2 - Halogen Acid Gas Amount - Min. pH = 4.3
European Directive Compliance	EU CE Mark
UK Regulation Compliance	UKCA Mark

History

Update and Revision	Revision Number: 0.227 Revision Date: 03-30-2023
---------------------	--